

# coastline industrial coatings, inc.

3401 Fifth Street – Stafford, Texas 77477 (281) 499-0633

## AF-3250 Elastomeric Roof Coating

### FEATURES

- High Durability
- Meets all ASTM D 6083-97A requirements
- Excellent Flexibility and Elongation
- High Solids / Fast Dry
- Protects against atmospheric conditions including U.V.
- Conserves energy

### COMPOSITION

100% Acrylic Resin  
Pigmentation varies with color.  
Water-Based

### TYPICAL USES

- Exterior
- Aluminum / Galvanized Metal
- Structural Steel
- Concrete
- Polyurethane Foam

### PHYSICAL DATA

**COLOR:** WHITE  
**FINISH:** SATIN  
**COMPONENTS:** SINGLE  
**SOLIDS CONTENT:** VOL. 52%  
**FLAMMABILITY:** NON-FLAMMABLE  
**WEIGHT / GAL:** 10.2 LBS.  
**TEMPERATURE LIMIT:** 260° F  
**RECOMMENDED DFT:** 7 – 8 MILS  
**THEORETICAL COVERAGE:** 834 SQ. FT. / GAL (1 MIL)  
**FLASH POINT:** NONE  
**DRY TIME @ 55% RH & 77° F:**  
TOUCH – 30 MIN.  
HANDLE – 2 HOUR  
**SHELF LIFE:** 1 YEAR MIN. (UNOPENED)

### SURFACE PREPARATION

Prior to coating, all surfaces must be clean, dry and free of all contaminants.

### APPLICATION DATA

**NO PRIMER REQUIRED:** CONCRETE, ALUMINUM, POLYURETHANE FOAM  
**APPLIED OVER PRIMED STEEL:** P-34  
**METHOD:** BRUSH, ROLL OR SPRAY  
**MIXING RATIO:** N/A  
**POT LIFE:** N/A

### APPLICATION PROCEDURE

\*\*\*SEE APPLICATION GUIDE

**THINNER:** NOT REQUIRED  
**EQUIPMENT CLEANER:** SOAP AND WARM WATER

### SHIPPING DATA

**PACKAGING UNITS:**  
1 gal. unit, 5 gal. unit, 55 gal. unit

### LIMITATION OF LIABILITY

COASTLINE's liability on any claim of any kind, including claims based upon COASTLINE's negligence or strict liability, for any loss or damage arising out of, connected with or resulting from the use of the products, shall in no case exceed the purchase price allowable to the products or parts thereof which give rise to the claim. In no event shall COASTLINE be liable for consequential or incidental damages.