

coastline industrial coatings, inc.

3401 Fifth Street – Stafford, Texas 77477 (281) 499-0633

AF-550 High Performance Latex Enamel

FEATURES

- Durable finish
- Maintains uniform gloss
- Excellent weather ability
- Fast Dry / Non-Fading
- Protects against U.V. and mildew
- With stands repeated washes

COMPOSITION

Acrylic Resin
Pigmentation varies with color.

TYPICAL USES

- Interior and Exterior walls
- Architectural maintenance paint
- Commercial buildings, warehouses
- School, hotels, hospitals

PHYSICAL DATA

COLOR: VARIOUS
FINISH: GLOSS / SEMI-GLOSS
COMPONENTS: SINGLE
SOLIDS CONTENT: VOL. 44%
VOC: 0.40
WEIGHT / GAL: 10.5 LBS.
TEMPERATURE LIMIT: 212° F
RECOMMENDED DFT: 2 – 3 MILS
THEORETICAL COVERAGE: 704 SQ. FT. / GAL (1 MIL)
FLASH POINT: N/A
DRY TIME @ 55% RH & 77° F:
TOUCH – 30 MIN.
HANDLE – 1 HOUR
SHELF LIFE: 1 YEAR MIN. (UNOPENED)

SURFACE PREPARATION

Prior to coating, all surfaces must be clean, dry and free of all contaminants.

APPLICATION DATA

METHOD: BRUSH, ROLL OR SPRAY
MIXING RATIO: N/A
POT LIFE: N/A

APPLICATION PROCEDURE

1. Flush all equipment with water
2. Mix product thoroughly
3. Thin only if necessary for workability
4. For airless spray. Adjust pressure as needed
5. Apply a wet coat in ever parallel passes, overlap 50 percent to avoid holidays, bare areas and pinholes.
6. Application of 35 mils, wet film thickness will normally provide 2-3 mils dry film
7. Clean all equipment with water immediately after use

THINNER: WATER

EQUIPMENT CLEANER: warm soapy water

SHIPPING DATA

PACKAGING UNITS:
1 gal. unit, 5 gal. unit, 55 gal. unit

LIMITATION OF LIABILITY

COASTLINE's liability on any claim of any kind, including claims based upon COASTLINE's negligence or strict liability, for any loss or damage arising out of, connected with or resulting from the use of the products, shall in no case exceed the purchase price allowable to the products or parts thereof which give rise to the claim. In no event shall COASTLINE be liable for consequential or incidental damages.